



WELDING TOGETHER



QUBOX PULSE

SINCE 1950





QUBOX / QUBOX PULSE



MIG/MAG



MMA



TIG (WIG)

QUBOX



MIG/MAG



PULSED



MMA



TIG (WIG)

QUBOX PULSE

SYNERGIC MULTIPROCESS INVERTER EQUIPMENT WITH SEPARATE WIRE FEEDER

QUBOX and QUBOX PULSE series multiprocess equipment are characterized by a synergic digital control and inverter technology integrated into a sturdy and functional metallic structure, with a separate wire feeder.


Technologically advanced, robust and easy-to-use, they allow high quality welding in MMA, TIG with “Lift” mode, MIG-MAG and with the QUBOX PULSE models, also in PULSED MIG.

QUBOX and QUBOX PULSED equipment also allow less experienced operators to easily adjust all welding parameters in an intuitive way. Once the wished program has been selected, the welding control automatically sets the best parameters based on the material type, wire diameter and gas being used, result of CEA's know-how acquired in 70 years' experience. These power sources represent the best choice in all industrial fields for all qualified applications requiring high precision and repeatability of the welding results, such as medium and large fabrication work, shipyards and steel erection. QUBOX W and QUBOX W PULSE equipment are fitted with integrated water cooling unit.




VISION.ARC

vision.ARC is the innovative welding arc control developed by CEA granting a short arc extremely stable and precise in spite of any change of the external conditions. vision.ARC ensures outstanding performances, impossible to be obtained by traditional power sources.



VISION.PULSE (QUBOX PULSE)

Vision.PULSE permits a short arc pulse welding, constantly controlled, by optimizing the results of traditional pulse welding. This enables to reduce the high heat input, typical in pulse welding, with a consequent reduction in distortions, an improvement in the puddle and considerable increase in welding speed too.



WSC - WIRE START CONTROL

WSC wire start control prevents any possible wire sticking to the workpiece or torch nozzle, by always ensuring a precise and “soft” arc striking.

BURN BACK CONTROL

At the end of each weld, in any condition and with any metal, the digital control ensures a perfect wire cut thus avoiding the formation of the typical “wire globule” by ensuring the subsequent best arc striking

SIMPLE AUTOAMTION

Standard equipped with analogic-digital I/O, QUBOX PULSE power sources can be easily integrated into automated welding equipment without any expensive and sophisticated external interfaces usually necessarily supplied for robotics.

UP/DOWN AND DIGITORCH

Possibility of working by means of up/down torches and Digitorch to easily adjust main welding parameters at the work place.

FEATURES

- ▶ Multiprocess power sources: MMA TIG LIFT - MIG/MAG Synergic & Manual and for QUBOX PULSE: PULSED MIG
- ▶ Parameter control directly from the wire feeder
- ▶ Digital control of the welding parameters with synergic curves preset according to used type of material, gas and wire diameter
- ▶ Ability to store personalized welding parameters up to 99 JOBS
- ▶ Smart PROGRAM™ key for quickly selecting any program
- ▶ Feeding mechanism with 4 rolls of large diameter for a precise and constant wire driving
- ▶ Double groove rolls replaceable without any tool
- ▶ “Energy saving” function to operate the power source cooling fan and torch water cooling only when necessary
- ▶ Excellent arc striking always precise and efficient
- ▶ Ability to partially or totally lock the equipment with access key by password
- ▶ Reduced energy consumption
- ▶ Trouble shooting auto-diagnosis feature
- ▶ Great robustness due to solid metallic main structure
- ▶ Control rack protection cover on the wire feeder
- ▶ Initial and final crater control
- ▶ VRD – Voltage Reduction Device
- ▶ Water cooling equipment integrated into the power source (W version)

WIRE FEEDER QF 4W / QF 7 PRO DRIVE

- Digital control of all parameters, duly protected by a cover
- Professional wire feeding mechanism with 4 rolls of large diameter for a precise and constant wire driving
- Graduated knob to achieve the most correct value of the wire pressure, which remains unchanged also after any arm opening and closing
- Double groove rolls replaceable without any tool
- Lodging for wire spools up to 300 mm diameter
- Led light in the feeder compartment (QF7 Pro Drive)
- Inspection window in the spool cover (QF7 Pro Drive)
- HK1 Hanging Kit (QF 7 Pro Drive)

QUBOX equipment, in the air cooled version, offer the possibility of utilizing up to 40 m long interconnecting cables from the power source to the feeder.



DIGITORCH

The DIGITORCH torches allow you to view the main welding parameters directly on the torch display. Furthermore, depending on the selected operating mode, it is possible to switch from one program to another or increase or decrease the parameters of the synergic curve in use.



The QUBOX PULSE models are available in: **STANDARD** configurations, designed for the most used welding applications, and **PREMIUM**, equipped with the innovative welding processes **vision.COLD**, **vision.ULTRASPEED** and **vision.POWER**. On this second version is standard the package of special **ECP** curves dedicated to those who want a system with higher level welding performance and who is not willing to give up the flexibility to weld different materials

QUBOX PULSE PREMIUM



To weld thin thickness laminations with low heat transfer



For high speed welding



For a more accurate welding in pipe first root pass.



For a more concentrated arc and deeper penetration on medium and thick thickness



ACCESSORIES

- Up/Down torches
- WK1 kit of standard wheels (only with QF4)
- WK2 kit of extra large wheels (with QF4 and QF7)
- WK4 kit of standard wheels (only with QF7)
- Hanging Kit HK1
- Adjustable torch support
- Wire feeder holding support
- Dust filter
- Remote control RC 178



TECHNICAL DATA		QUBOX			QUBOX PULSE			
		400	400W	500W	335	335W	405W	505W
Three phase input 50/60 Hz	V ^{+20%} / _{-20%}	400		400	400		400	400
Input Power @ I2 Max	kVA	22		29,5	17,5		22,5	29,5
Delayed Fuse (I eff)	A	32		40	25		32	40
Power Factor / cos φ		0,7/0,99		0,72/0,99	0,70/0,99		0,70/0,99	0,72/0,99
Efficiency Degree		0,88		0,89	0,88		0,88	0,89
Open circuit voltage	V	62		62	62		62	62
Current range	A	10 - 400		10 - 500	10 - 330		10 - 400	10 - 500
Duty cycle at (40°C)	A 100%	350		420	300		350	420
	A 60%	400		500	330		400	500
Wires	Ø mm	0,6 - 1,6		0,6 - 1,6	0,6 - 1,6		0,6 - 1,6	0,6 - 1,6
Standards		EN 60974-1 • EN 60974-5 • EN 60974-10			EN 60974-1 • EN 60974-5 • EN 60974-10			
		[S]			[S]			
Protection Class	IP	23 S		23 S	23 S		23 S	23 S
Insulation Class		H		H	H		H	H
Dimensions	↗ mm	1030		1030	1030		1030	1030
	→ mm	950		950	950		950	950
	↑ mm	515		515	515		515	515
Weight	kg	70	80	86	70	80	80	86

